

A background image of a person in a yellow life vest carrying a surfboard on a beach. The person's surfboard has 'PicoPix' and 'DON'T STOP BELIEVING' written on it. The life vest has 'VEGAS 11' on it. The scene is set on a sandy beach with a forested hillside in the background.

PHILIPS

PicoPix

Project your life

PicoPix pocket projector

This brilliant little companion is the ultimate device for on-the-go. Equipped with HDMI and USB interface it's never been so easy to project videos and pictures. The USBQuickLink offers a USB plug and socket to charge the device. No matter where you are – project your life with the PPX 4150.

Excellent image quality

- WavEngine with LED technology surprises by crystal clear pictures in brilliant colors
Project HD videos and images up to 60" (152 cm) in size

High usability

- HDMI interface & support of MHL for mobile devices like smartphones and tablets

USBQuickLink

- USB plug and socket for power and easy connection



PPX 4150

PPX 4150

Technology

Display technology	DLP WavEngine
Light Source	RGB LED
LED light sources	last over 30,000 hours
Brightness	up to 50 Lumen
Contrast ratio	1300:1
Resolution	640 x 360 pixel
Throw ratio	2.2:1
Screen size (diagonal)	25 cm–152 cm 10"–60"
Screen distance	48 cm–285 cm 19"–112"
Aspect ratio	16:9
Projection modes	front; rear; front ceiling; rear ceiling
Wall colour correction	yes (white, yellow, pink green, blue)
Focus adjustment	manual
Noise level	< 28 dba

Sound

Built-in speakers	1 Watt (max)
-------------------	--------------

Connection

Connectivity	USB: Charging Firmware upgrade HDMI: mini HDMI with HDCP Output audio: 3.5 mm audio out jack for headphones
--------------	---

Power source

Battery	Internal battery: 1800mAh
	Battery life:
	Optimal mode: 1,5 hours
	Eco mode: 2 hours

Logistic Data

Packaging dimensions	Packed (W x D x H): 130 x 86 x 65 mm 5.12 x 3.39 x 2.56 inch Unpacked (W x D x H): 97 x 54 x 17 mm 3.81 x 2.12 x 0.67 inch
Weight	Packed: 192 g / 6.77 oz Unpacked: 129 g / 4.55 oz
Temperature range	Operation: 5–35° C / 41 – 95°F Storage packed: -25–60° C / -13 – 140°F Storage unpacked: 0–45° C / 32 – 113°F
Relative humidity	Operation: 15–85 % RH Storage packed: 5–93 % RH Storage unpacked: 15–85 % RH
Standard package includes	PPX 4150 Quick start guide Warranty card Mini-HDMI to HDMI cable



Photo Credit: Toby Bromwich

PHILIPS and the PHILIPS' Shield Emblem are registered trademarks of Koninklijke Philips N.V. and are used by Sagemcom under license from Koninklijke Philips N.V.

© 2014 Sagemcom Austria GmbH.

All rights reserved. The information and specifications included are subject to change without prior notice. Sagemcom tries to ensure that all information in this document is correct, but does not accept liability for error or omission.



PPX 4150
 9 NC: 253619960
 UPC: 6 09585 24869 4
 EAN: 3425160334562

www.philips.com/screeneo
www.youtube.com/user/ScreeneoTV
www.twitter.com/Screeneo
www.facebook.com/Screeneo